

DECKS • SIDINGS • FENCES • ROOFS • LOG HOMES

envirolast

BEAUTIFUL WOOD COATINGS

XT2 WOOD STAIN AND SEAL



Decks

Sidings

Log Homes

Furniture

Docks



Double Durability
on Wood Decks!

Exterior deck and
siding stain

Linseed/acrylic/
urethane hybrid resin

Zero VOC/Zero HAPS

Formulated for
sensitive individuals

Excellent for interior
uses

Ultra quick re-coat

Will not darken
on decks

envirolast

BEAUTIFUL WOOD COATINGS

XT2 WOOD STAIN AND SEAL

Www. Envirolast.com

P.O. Box 3039

Olympic Valley, Ca 96146

FEATURES

Deep Penetration	Alkyd Performance
Soap Water Cleanup	Zero VOC
Full Transparency	High Durability
Trans-Oxide Pigments	Apply 32°-100° F
Excellent Adhesion	Quick Applications
Won't Raise Grain	Very Low Odor

GENERAL PROPERTIES

Envirolast XT2™ is formulated using self-emulsified, water-borne, long oil/ alkyd/urethane. The unique formula allows for the penetration, performance and beauty of an alkyd wood sealer; in a safe, ultra-low odor formula and the easy soap-water cleanup of a waterborne system.

RECOMMENDED FOR

Envirolast XT2 is recommended for all exterior and interior wood surfaces requiring a semi-transparent or semi-solid pigmented finish, with little to no odor, zero VOC and fast application time. Envirolast XT2 has excellent adhesion properties and may be applied over most existing wood finishes. Previously failing or peeling finishes may continue to do so, even after Envirolast XT2 is applied as a maintenance coat.

LIMITATIONS

Envirolast XT2 is fully transparent even in multiple coats which allow UV rays to pass through the coating, highlighting the woods grain. Typically the coating will fail *top down* allowing for maintenance coats to be applied, requiring little or no restoration of the woods surface. Decking and horizontal surfaces may require more maintenance than horizontal surfaces. The condition of wood and exposure to sun and water may vary performance greatly.

Labor Saving Benefits

- Soap and Water Cleanup
- Near Immediate Re-Coat Time
- Compatible with Most Wood Sealers
- Easy Prep for Maintenance Coats

6 Transparent Oxide Colorants for 5 Gallon Base

YELLOW CEDAR 100% Yellow	RED CEDAR 75% Yellow/25% Red
BUTTERSCOTCH 87.5% Yellow/ 12.5% Brown	TARNISHED GOLD 50% Yellow/50% Raw Umber
SADDLEBAG 100% Brown	RUSTICA BROWN 50% Brown/37.5% Red/12.5% Black

Environmentally responsible Product

Zero metallic drier compounds	Leaves residue when stain decomposes. Can cause Heavy metal poisoning
Contains apprx. 50% renewable resources	Uses renewable natural oils
Zero VOC, zero exempt VOC	Such as Acetone or TBaC TBaC being on Cal EPA health watch list
Zero Anti- Fungal agents	Known to be Carcinogenic

Technical Data

Envirolast XT2 Clear Base

Generic Type	Self -Emulsified Oil/ Alkyd/Urethane
Pigment Type	Trans-Oxide or Universal
Pigment Quantity	6-18 oz. per 5 gallons
Volume Solids	25% by volume and weight
Coverage Rough Wood	250 sq. ft. per gallon
Coverage Smooth Wood	350 sq. ft. per gallon
Tack Time	15-30 minutes
Water Resistance	12-24 hours
Surface Temperature	32°-100° F
Flash Point	Non-Flammable
Cleanup	Hand Soap & Water
Strip With	Potassium Hydroxide Cleaner
Flash Point	Celsius >100